

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Express Mail No.: EL 990505137 US
In re application of: THOMPSON et al.
Serial No.: 0 /
Filed: Herewith
For: HEAT SINK

Group No.:

Examiner:

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country : Great Britain
Application Number : 0309719.3
Filing Date : April 29, 2003

WARNING: "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 CFR 1.4(f) (emphasis added.)

Reg. No.: 44,695


SIGNATURE OF ATTORNEY

Joseph V. Gamberdell

Type or print name of attorney

Tel. No.: (203) 259-1800

Perman & Green, LLP

Customer No.: 2512

P.O. Address

425 Post Road, Fairfield, CT 06824

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63.

(Transmittal of Certified Copy [5-4])

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 18 July 2003

THIS PAGE BLANK (USPTO)



29APR03 E803424-1 D10064
P01/7700 0.00-0309719.3

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference 30020643 GB-01

2. Patent application number
(The Patent Office will fill in this part)

0309719.3

29 APR 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Agilent Technologies, Inc.
395 Page Mill Road
P.O. Box 10395
Palo Alto
CA 94303-0870
USA

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

A Delaware corporation

7771868001

TS

4. Title of the invention Heat Sink

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Agilent Technologies UK Limited
Legal Department - IP Practice Group
Eskdale Road, Winnersh Triangle
Wokingham
Berkshire
RG41 5DZ

Patents ADP number (if you know it)

7771884052

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	8
Claim(s)	2
Abstract	1
Drawing(s)	6 + 6 <i>14</i>

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 1

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.
- | | | |
|-----------------|---------------------|-----------------|
| Signature | <i>James Lenney</i> | Date |
| Dr James LENNEY | | 28th April 2003 |
12. Name and daytime telephone number of person to contact in the United Kingdom
- | | |
|---------------|---------------|
| Pauline Jones | 0118 927 4423 |
|---------------|---------------|

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

HEAT SINK

This invention relates to heat sinks for use with electronic devices and in particular for use with modular electronic
5 devices that are received within a rack or a bay.

As the density of transistors in electronic devices and the power output levels and switching speeds of opto-electronic devices increase, there is a corresponding increase in the
10 heat generated by such devices. As the electronic and/or opto-electronic devices are typically stored within enclosures the heat generated by their operation can lead to significant problems as some devices may be destroyed if their core temperature is too great, or the performance of
15 the device may be substantially degraded. Known techniques used to control the temperature of individual devices include the use of heat sinks, heat pipes and fans, and fans are also used to draw cool air into the enclosure holding the electronic devices and to expel warm air from the enclosure.

20 It has been observed that these techniques, while generally being sufficient to control the generation of heat and to mitigate any effects caused by increased temperature, are less efficacious when used with modular electronic devices.
25 An example of such a device is an opto-electronic transmission module that is received within an equipment rack. In order to facilitate maintenance and the fast replacement of failed modules, the modules, which are often referred to as pluggable modules, can be removed from or
30 inserted into a bay within an equipment rack or mounting. As the module is slid into and out of the bay it is problematic to maintain an efficient thermal connection between the

module and a heat sink, or other cooling equipment, that is provided inside the equipment rack so as to be in contact with an inserted module. If a module is replaced by a module that dissipates more heat then it may be necessary to access
5 the interior of the equipment rack in order to change the cooling equipment.

According to a first aspect of the present invention there is provided a heat sink arrangement configured to receive an
10 equipment module, the heat sink arrangement comprising alignment means to engage with the heat sink arrangement and a pivotable heat sink, the heat sink being pivoted by the insertion of the equipment module such that a surface of the heat sink is brought into contact with a surface of the
15 equipment module.

The heat sink arrangement may further comprise an aperture for receiving the equipment module and the pivotable heat sink may be inclined such that the surface of the pivotable
20 heat sink that makes contact with the equipment module is presented towards the aperture. One or more of the faces of the heat sink may comprise one or more protrusions and the support for the pivotable heat sink may comprise a heat pipe. The pivotable heat sink may further comprise gas- or liquid-
25 cooling apparatus. The surface of the pivotable heat sink that makes contact with the equipment module may comprise a material that increases the diffusion of heat from the equipment module.

30 According to a second aspect of the present invention there is provided an equipment module for use with a heat sink arrangement according to any preceding claim, the equipment

module having a substantially cuboidal form and comprising guide means for engaging with the alignment means of the heat sink arrangement. The surface of the equipment module that makes contact with the pivotable heat sink may comprise a material that increases the diffusion of heat from the equipment module and/or a material having a low coefficient of friction. The surface of the equipment module that makes contact with the pivotable heat sink may comprise an inclined region.

10

Figures 1 to 4 shows a schematic depiction of a heat sink arrangement 100 according to the present invention and an equipment module 10 that may be inserted into and removed from the heat sink arrangement 100. The equipment module 10 comprises internal communications interface 12, guide portions 14 and external communications interface 16. The internal communications interface is designed so as to be received within a corresponding interface within the heat sink arrangement 100 (see below) that is in communication with a transmission line or further piece of equipment. The external communications interface 16 is located on the front face of the equipment module that is not received within the heat sink arrangement for onward communication with a transmission line or a further piece of equipment. The guide portions 14 are preferably located on both side faces of the equipment module and are designed to engage with complementary features provided with the heat sink arrangement (see below) to assist the mechanical alignment of the equipment module within the heat sink arrangement and to secure the equipment module when fully inserted within the heat sink arrangement.

20

25

30

The heat sink arrangement 100 is received within an equipment rack (not shown) and comprises a front plate 110 comprising an aperture 115, a pivotable heat sink 120, support means 130, pivot pin 140, base 150 and equipment rack communications interface 160. The support means 130 comprises alignment means 132 and pivot arms 135, the pivot pin being received in and connected between the two pivot arms (referring to Figure 1, the second pivot arm is hidden from view behind the heat sink 120). The support means 130 is mounted on the base 150 and the front plate is mounted on the base and the support means in a plane that is substantially orthogonal to the plane of the base. The pivotable heat sink is held by the pivot pin 140 and is free to pivot. The default position of the heat sink is to be pivoted slightly such that the flat side of the heat sink is pointed towards the aperture 115 within the front plate 110. This can be achieved by placing the pivot pin at an off-centre position on the heat sink, by designing the heat sink to have an asymmetric centre of gravity or by adding a small biasing spring to return the heat sink to the desired position when an equipment module is not present.

The equipment rack communications interface 160 is mounted within the support means and is positioned such that when an equipment module 10 is inserted into the heat sink arrangement 100 the internal communications interface is brought into communication with the equipment rack communications interface. The alignment means 132 of the support means are provided to engage with the guide portions of the equipment module such that when the equipment module is inserted into the heat sink arrangement the internal communications interface will be in alignment with the

equipment rack communications interface. In Figure 1 the guide portions comprise upstanding tab portions and the alignment means comprise tabs which are bent downwardly to engage with the guide portions but it will be understood that other geometries and forms of guide portions and alignment means may be used. An advantage of the arrangement shown in Figures 1-4 is that the alignment means provide EMI shielding for the equipment module.

When an equipment module is inserted into the heat sink arrangement, the upper face of the module will cause the heat sink, 120 to pivot, bringing the lower surface of the heat sink into contact with the upper surface of the equipment module (see Figures 3 and 4). The pivoting arrangement increases the contact area between the equipment module and the heat sink, increasing the transfer of heat between the equipment module and the heat sink.

Figures 3 and 4 show schematic depictions of an equipment module 10 inserted into a heat sink arrangement 100 according to the present invention, with Figure 3 showing a perspective view and Figure 4 showing a side view. In a preferred embodiment of the invention, the pivot pin 140 may comprise a heat pipe that can carry heat away from the heat sink 120.

25

Figure 5 shows a schematic depiction of the side view of an alternative embodiment of the present invention in which the equipment module 20 differs from the equipment module 10 described above with reference to Figures 1 to 4 in that the equipment module 20 has a non-uniform cross-section. The contact face (i.e. the face that is brought into contact with the heat sink) is divided into a first flat region 27 and a

30

second angled region 28, the angled region being closest to the face of the equipment module 20 that is inserted into the heat sink arrangement. . It has been found that the angled region 28 assists in bringing the equipment module 20 into
5 contact with the heat sink.

The contact area between the equipment module and the heat sink should be sufficient to couple the heat dissipated by the equipment module but it is possible to improve the
10 thermal contact by attaching an interface material to the surface of the heat sink that come into contact with the equipment module, such as a thermal matting or a suitable phase change material. Although the heat sink 120 shown in Figures 1-4 comprises a plurality of fins in order to
15 increase heat dissipation, it will be understood that the heat sink could alternatively be a flat heat spreader, or that fins could be attached to a limited region of the heat sink. Furthermore, additional techniques and technology may be used to provide an increased degree of heat dissipation;
20 fans may be mounted to the heat sink; the pivot pin 140 may comprise a heat pipe, the heat sink may be cooled using a gas- or liquid-cooling system, the heat sink may comprise one or more regions that act as planar heat pipes, etc.

25 The material used to form the upper surface of the equipment module preferably has one or more of the following characteristics:

- a low coefficient of friction to ease insertion and extraction of the module;
- 30 • a high thermal conductivity to increase the dissipation of heat away from the module and towards the heat sink;
- sufficient mechanical strength to withstand repeated

insertion and extraction of the module; and

- a degree of mechanical compression that will reduce the mechanical tolerances required for the components required.

5

A suitable material is Sarcon® GHR-AD from Fujipoly Europe Ltd., which comprises a glass-reinforced silicone rubber having a high thermal conductivity. The material may be provided with an adhesive coating for connection to the equipment module or other surfaces. Sarcon® GHR-AD also has a relatively low coefficient of friction although it is possible that a material having a lower coefficient of friction, such as PTFE, may be added to the Sarcon®.

10

15 Figure 6 shows a schematic depiction of a further embodiment of the present invention. Heat sink arrangement 200 comprises heat sinks 220a, 220b, 220c, 220d, which are all connected by pivot pin 240. Each heat sink has an associated aperture 215a, 215b, 215c and 215d and in Figure 6 apertures 20 215a, 215b and 215d contain equipment modules 10a, 10b and 10d respectively, whilst aperture 215c is vacant. As the heat sinks are connected by the pivot pin, the pin will assist in the distribution of heat between adjacent heat sinks, also making use of heat sinks that are not in contact 25 with an equipment module (such as heat sink 215c as shown in Figure 6). It will be readily understood that the invention may be adapted to incorporate any number of equipment modules, as equipment racks used in telecommunications and data communications applications may comprise 48 modules or 30 more.

It will be understood that the equipment module may comprise

electronic equipment, electro-optical equipment or all optical equipment. Although the invention has been described above with specific reference to modular units such as may be used in data communications, it will be understood that the
5 present invention may be applied to other applications where cooling may be required, for example for cooling CPUs, hard drives or other devices in computers.

CLAIMS

1. A heat sink arrangement configured to receive an
5 equipment module, the heat sink arrangement comprising
alignment means to engage with the heat sink arrangement and
a pivotable heat sink, the heat sink being pivoted by the
insertion of the equipment module such that a surface of the
heat sink is brought into contact with a surface of the
10 equipment module.

2. A heat sink arrangement according to claim 1, wherein
the heat sink arrangement further comprises an aperture for
receiving the equipment module and the pivotable heat sink is
15 inclined such that the surface of the pivotable heat sink
that makes contact with the equipment module is presented
towards the aperture.

3. A heat sink arrangement according to claim 1 or claim 2,
20 wherein one or more of the faces of the heat sink comprise
one or more protrusions.

4. A heat sink arrangement according to any preceding claim
in which the support for the pivotable heat sink comprises a
25 heat pipe.

5. A heat sink arrangement according to any preceding
claim, wherein the pivotable heat sink further comprises gas-
or liquid-cooling apparatus.

30

6. A heat sink arrangement according to any preceding claim
wherein the surface of the pivotable heat sink that makes

contact with the equipment module comprises a material that increases the diffusion of heat from the equipment module.

7. An equipment module for use with a heat sink arrangement
5 according to any preceding claim, the equipment module having a substantially cuboidal form and comprising guide means for engaging with the alignment means of the heat sink arrangement.
- 10 8. An equipment module according to claim 7, wherein the surface of the equipment module that makes contact with the pivotable heat sink comprises a material that increases the diffusion of heat from the equipment module.
- 15 9. An equipment module according to claim 7 or claim 8, wherein the surface of the equipment module that makes contact with the pivotable heat sink comprises a material having a low coefficient of friction.
- 20 10. An equipment module according to any of claims 7 to 9, wherein the surface of the equipment module that makes contact with the pivotable heat sink comprises an inclined region.

ABSTRACT

A heat sink arrangement for modular electronic and/or opto-electronic equipment is provided. The equipment module is
5 inserted into an interface and a heat sink is pivotably arranged so as to be brought into contact with the inserted module. The equipment module may have an angled, or partially angled, so as to assist in bringing the module in contact with the heat sink.

10

Figure 1.

1/6




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6